

View Online at <https://aerobasegroup.com/nsn/5950-00-240-0401>

Mounting Slot Width:

0.687 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

25.0 kilovolt-ampere single component

Distance Between Mounting Facility Centers:

24.000 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and slot single group

Cooling Method:

Self-cooled

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Voltage:

2.16 ac kilovolts single component single primary and 2.22 ac kilovolts single component single primary and 2.28 ac kilovolts single component single primary and 2.34 ac kilovolts single component single primary and 2.40 ac kilovolts single component single primary and 3.64 ac kilovolts single component single primary and 3.75 ac kilovolts single component single primary and 3.385 ac kilovolts single component single primary and 3.95 ac kilovolts single component single primary and 4.16 ac kilovolts single component single primary

Terminal Type And Quantity:

3 standoff insulator and 2 standoff, solderless lug

Specification Or Standard:

1 type and 1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0