

View Online at <https://aerobasegroup.com/nsn/5950-00-240-0403>

Mounting Slot Width:

0.781 inches single group and 0.781 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

50.0 kilovolt-ampere single component

Distance Between Mounting Facility Centers:

23.250 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Slot single group

Cooling Method:

Self-cooled

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Voltage:

2.16 ac kilovolts single component single primary and 2.22 ac kilovolts single component single primary and 2.28 ac kilovolts single component single primary and 2.34 ac kilovolts single component single primary and 2.40 ac kilovolts single component single primary and 3.64 ac kilovolts single component single primary and 3.75 ac kilovolts single component single primary and 3.85 ac kilovolts single component single primary and 3.95 ac kilovolts single component single primary and 4.16 ac kilovolts single component single primary

Special Features:

Taps brought to no-load tap changer operating handle under cover

Terminal Type And Quantity:

3 standoff insulator and 2 standoff, solderless lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0