# NSN 5950-00-240-6931

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-240-6931

# Reliability Indicator:

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.188 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

# Mounting Hole Diameter:

0.161 inches single group

#### **Frequency Rating:**

57.0 hertz single component and 63.0 hertz single component

# Input-output Phase Relationship:

Single phase to single phase single component

# Winding Shielding Method:

Internal shield brought out to terminal single component

# **Body Length:**

# 2.938 inches

**Body Width:** 

2.312 inches

#### **Body Height:**

2.438 inches

# Maximum Operating Temp:

85.0 degrees celsius

#### Inclosure Type:

Open

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Flange single group and unthreaded hole single group

# Winding Function And Quantity:

1 primary single component and 1 secondary single component

# Winding Operating Current:

170.0 milliamperes ac single component single secondary

# Winding Operating Voltage:

220.00 ac pounds per hour wet single component single secondary

# **Terminal Type And Quantity:**

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5950-00-240-6931

Power Transformer - Page 2 of 2

**Fiig:** A058b0

