NSN 5950-00-240-7976

Audio Frequency Transformer - Page 1 of 2



Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 2.125 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.750 inches single mounting facility single center group Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Center To Center Distance Between Mounting Facilities Parallel To Length: 2.125 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.750 inches single mounting facility single center group Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	View Online at https://aerobasegroup.com/nsn/5950-00-240-7976
Center To Center Distance Between Mounting Facilities Parallel To Length: 2.125 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.750 inches single mounting facility single center group Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Center To Center Distance Between Mounting Facilities Parallel To Length: 2.125 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.750 inches single mounting facility single center group Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Reliability Indicator:
2.125 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.750 inches single mounting facility single center group Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Center To Center Distance Between Mounting Facilities Parallel To Width: 1.750 inches single mounting facility single center group Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Not established
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.750 inches single mounting facility single center group Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Center To Center Distance Between Mounting Facilities Parallel To Width: 1.750 inches single mounting facility single center group Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches single mounting facility single center group Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	1.750 inches single mounting facility single center group Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	2.125 inches single mounting facility single center group
Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Overall Height: 3.625 inches Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Center To Center Distance Between Mounting Facilities Parallel To Width:
Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	1.750 inches single mounting facility single center group
Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Impedance Rating In Ohms: 5000.0 single component single primary Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Overall Height:
Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	3.625 inches
Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Frequency Rating: 150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Impedance Rating In Ohms:
150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	150.0 hertz single component and 3.0 kilohertz single component Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	5000.0 single component single primary
Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Maximum Transformer Power Rating: 15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Frequency Rating:
15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	15.0 watts single component Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	150.0 hertz single component and 3.0 kilohertz single component
Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Primary To Secondary Turn Ratio: 1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Maximum Transformer Power Rating:
1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	1 to 1-3/10 single component Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	15.0 watts single component
Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Body Length: 2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Primary To Secondary Turn Ratio:
2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	2.719 inches Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	1 to 1-3/10 single component
Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Body Width: 2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Body Length:
2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	2.391 inches Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	2.719 inches
Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Body Height: 2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Body Width:
2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	2.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	2.391 inches
Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Body Height:
Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	2.812 inches
Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Inclosure Type:
4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:	4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Fully enclosed
Mounting Method: Threaded stud single group Winding Function And Quantity:	Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	Mounting Facility Quantity:
Threaded stud single group Winding Function And Quantity:	Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component	4 single group
Winding Function And Quantity:	Winding Function And Quantity: 1 primary single component and 1 secondary single component	Mounting Method:
-	1 primary single component and 1 secondary single component	Threaded stud single group
1 primary single component and 1 secondary single component		Winding Function And Quantity:
	Thready Qty Per Inch (tpi):	1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):		Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-240-7976

Audio Frequency Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0