

View Online at <https://aerobasegroup.com/nsn/5950-00-241-0114>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.490 inches single mounting facility single center group and 3.510 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.740 inches single mounting facility single center group and 2.760 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 4.490 inches and 4.510 inches

Body Width:

Between 3.490 inches and 3.510 inches

Body Height:

Between 3.740 inches and 3.760 inches

Maximum Operating Temp:

75.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

3 primary single component and 8 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

6.5 amperes dc single component 3rd secondary

Winding Operating Voltage:

23.00 ac volts single component 1st secondary

Special Features:

3 primary windings; 8 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

35 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0