# NSN 5950-00-241-9611

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-241-9611

## Reliability Indicator:

Not established

## **Frequency Rating:**

50.0 hertz single component and 400.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single component

### Winding Shielding Method:

Internal shield grounded to inclosure single component

#### **Body Length:**

2.690 inches

**Body Width:** 

2.310 inches

**Body Height:** 

2.000 inches

#### **Distance Between Mounting Facility Centers:**

2.060 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

**Mounting Facility Quantity:** 

2 single group

Mounting Method:

Threaded stud single group

## Winding Function And Quantity:

2 primary single component and 4 secondary single component

### Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

### Winding Operating Current:

6.0 amperes ac single component 3rd secondary

### Winding Operating Voltage:

6.30 ac volts single component 3rd secondary115.00 ac volts single component all primary5.00 ac volts single component 4th secondary

#### Thread Series Designator:

Unc single group

### **Terminal Type And Quantity:**

14 wire lead

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

## NSN 5950-00-241-9611

Power Transformer - Page 2 of 2

**Fiig:** A058b0

