NSN 5950-00-242-0032

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-242-0032 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.500 inches single mounting facility single center group |
| Frequency Rating: |
| 60.0 hertz single component and 1.6 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure single component |
| Body Length: |
| 3.000 inches |
| Body Width: |
| 2.438 inches |
| Body Height: |
| 2.750 inches |
| Inclosure Type: |
| Hermetically sealed |
| Winding Function And Quantity: |
| 1 primary single component and 4 secondary single component |
| Winding Operating Current: |
| 600.0 milliamperes ac single component 3rd secondary |
| Winding Operating Voltage: |
| 6.30 ac pounds per hour wet single component 3rd secondary |
| Terminal Type And Quantity: |
| 10 standoff insulator |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A058b0