## NSN 5950-00-242-0032

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-242-0032             |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.500 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 60.0 hertz single component and 1.6 kilohertz single component            |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure single component                    |
| Body Length:  |
| 3.000 inches  |
| Body Width:   |
| 2.438 inches  |
| Body Height:  |
| 2.750 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Winding Function And Quantity:  |
| 1 primary single component and 4 secondary single component               |
| Winding Operating Current:  |
| 600.0 milliamperes ac single component 3rd secondary                      |
| Winding Operating Voltage:  |
| 6.30 ac pounds per hour wet single component 3rd secondary                |
| Terminal Type And Quantity:   |
| 10 standoff insulator   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |

Fiig: A058b0