## NSN 5950-00-242-2356

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-242-2356

View Online at https://aerobasegroup.com/nsn/5950-00-242-2356
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.812 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches single mounting facility single center group
Mounting Hole Diameter:
0.156 inches single group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Three phase to six phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
2.620 inches
Body Width:
2.250 inches
Body Height:
1.120 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
600.0 milliamperes ac single component single secondary
Winding Power Rating:
5.0 watts single component single primary
Winding Operating Voltage:
56.50 ac volts single component single secondary
Terminal Type And Quantity:
13 turret
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5950-00-242-2356

Power Transformer - Page 2 of 2



Fiig:

A058b0