NSN 5950-00-242-8996

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-242-8996

| Reliability Indicator: | |
|------------------------|--|
| Not established | |
| | stance Between Mounting Facilities Parallel To Length: |
| - | nounting facility single center group |
| | stance Between Mounting Facilities Parallel To Width: |
| 2.500 inches single n | nounting facility single center group |
| Frequency Rating: | |
| 57.0 hertz single com | nponent and 63.0 hertz single component |
| Input-output Phase | Relationship: |
| Single phase to single | e phase single component |
| Winding Shielding M | lethod: |
| Internal shield ground | led to inclosure single component |
| Body Length: | |
| 3.844 inches | |
| Body Width: | |
| 3.344 inches | |
| Body Height: | |
| 6.125 inches | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Facility Qu | uantity: |
| 4 single group | |
| Mounting Method: | |
| Unthreaded stud sing | le group |
| Winding Function A | nd Quantity: |
| 1 primary single comp | ponent and 2 secondary single component |
| Winding Operating (| Current: |
| 5.15 amperes ac sino | gle component 2nd secondary |
| Winding Operating \ | /oltage: |
| 6.50 ac volts single c | component 1st secondary |
| Terminal Type And (| Quantity: |
| 9 standoff, solder lug | 1 |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| | |