

View Online at <https://aerobasegroup.com/nsn/5950-00-243-1460>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.375 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.250 inches single mounting facility single center group

**Frequency Rating:**

360.0 hertz single component and 440.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and brought out to terminal single component

**Body Length:**

Between 1.813 inches and 1.938 inches

**Body Width:**

Between 1.688 inches and 1.813 inches

**Body Height:**

Between 2.313 inches and 2.438 inches

**Maximum Operating Temp:**

125.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 7 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

750.0 milliamperes dc single component 4th secondary

**Winding Operating Voltage:**

60.00 dc volts single component 2nd secondary 19.50 dc volts single component 4th secondary 19.50 dc volts single component 3rd secondary

**Special Features:**

1 primary, 7 secondary windings; all output voltages and currents are shown rectified; secondaries 5, 6, and 7 are rated but not included in write-up

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

17 turret or 17 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0