NSN 5950-00-243-1466

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-243-1466 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.375 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.250 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure single component |
| Body Length: |
| 2.438 inches |
| Body Width: |
| 1.812 inches |
| Body Height: |
| 1.938 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 5 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 850.0 milliamperes dc single component 2nd secondary |
| Winding Operating Voltage: |
| 35.00 dc volts single component 4th secondary66.00 dc volts single component 5th secondary104.00 ac volts single component single |
| primary and 126.00 ac volts single component single primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 12 wire hook |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5950-00-243-1466

Power Transformer - Page 2 of 2



Fiig:

A058b0