

View Online at <https://aerobasegroup.com/nsn/5950-00-243-1466>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.438 inches

Body Width:

1.812 inches

Body Height:

1.938 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

850.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

35.00 dc volts single component 4th secondary 66.00 dc volts single component 5th secondary 104.00 ac volts single component single primary and 126.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0