

View Online at <https://aerobasegroup.com/nsn/5950-00-243-1512>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.995 inches single mounting facility single center group and 3.005 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.745 inches single mounting facility single center group and 3.755 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 4.495 inches and 4.505 inches

Body Width:

Between 3.745 inches and 3.755 inches

Body Height:

Between 4.745 inches and 4.755 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 7 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

660.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

77.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component 4th secondary

Special Features:

Two primary windings and seven secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0