NSN 5950-00-243-5678

Vibrator Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-243-5678

Reliability Indicator:	
Not established	
Center To Center Distance Between Mounting Facilities Parallel To Lengtl	h
3.750 inches single mounting facility single center group	
Center To Center Distance Between Mounting Facilities Parallel To Width:	:
3.000 inches single mounting facility single center group	
Frequency Rating:	
120.0 hertz single component	
Winding Shielding Method:	
Internal shield grounded to inclosure single component	
Body Length:	
4.812 inches	
Body Width:	
4.000 inches	
Body Height:	
6.000 inches	
Inclosure Type:	
Hermetically sealed	
Mounting Facility Quantity:	
4 single group	
Mounting Method:	
Threaded stud single group	
Winding Function And Quantity:	
1 primary single component and 2 secondary single component	
Thready Qty Per Inch (tpi):	
20 single group	
Thread Size:	
0.250 inches single group	
Winding Operating Current:	
3.0 amperes ac single component 1st secondary	
Winding Operating Voltage:	
700.00 ac volts single component 2nd secondary	
Thread Series Designator:	
Unc single group	
Terminal Type And Quantity:	
10 standoff, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	

No

Demilitarization:

NSN 5950-00-243-5678

Vibrator Power Transformer - Page 2 of 2



Fiig:

A058b0