NSN 5950-00-243-8422

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-243-8422 **Reliability Indicator:** Not established Frequency Rating: 380.0 hertz single component and 1600.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component **Body Length:** 2.250 inches **Body Width:** 1.938 inches **Body Height:** 2.031 inches **Distance Between Mounting Facility Centers:** 1.031 inches single mounting facility single center group **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 2 single group **Mounting Method:** Threaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group **Thread Size:** 0.138 inches single group **Winding Operating Current:** 7.0 amperes ac single component 1st secondary **Winding Operating Voltage:** 6.30 ac volts single component 2nd secondary6.30 ac volts single component 1st secondary **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 8 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5950-00-243-8422

Power Transformer - Page 2 of 2



Fiig:

A058b0