NSN 5950-00-244-4428Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-244-4428 |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.375 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.875 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.166 inches single group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure single component |
| Body Length: |
| 2.000 inches |
| Body Width: |
| 1.750 inches |
| Body Height: |
| 3.000 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 5 secondary single component |
| Winding Operating Voltage: |
| 115.00 ac volts single component single primary |
| Terminal Type And Quantity: |
| 13 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization: No

Fiig:

A058b0