

View Online at <https://aerobasegroup.com/nsn/5950-00-244-5447>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.438 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.594 inches

Body Width:

2.688 inches

Body Height:

5.344 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

8.0 amperes ac single component single secondary

Winding Operating Voltage:

6.40 ac volts single component single secondary 115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0