

View Online at <https://aerobasegroup.com/nsn/5950-00-244-5529>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.438 inches single mounting facility single center group

Overall Height:

5.344 inches

Overall Width:

4.688 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

4.844 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

3.2 amperes ac single component single secondary

Winding Operating Voltage:

28.00 ac volts single component single secondary and 30.00 ac volts single component single secondary and 32.00 ac volts single component single secondary and 34.00 ac volts single component single secondary and 36.00 ac volts single component single secondary and 38.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0