

View Online at <https://aerobasegroup.com/nsn/5950-00-244-5531>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.594 inches

Body Width:

3.438 inches

Body Height:

5.312 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.5 amperes ac single component single secondary

Winding Operating Voltage:

2.00 ac volts single component single secondary and 4.00 ac volts single component single secondary and 6.00 ac volts single component single secondary and 10.00 ac volts single component single secondary and 12.00 ac volts single component single secondary and 42.00 ac volts single component single secondary

Terminal Type And Quantity:

10 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0