## NSN 5950-00-244-5641

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-244-5641

view Online at https://aerobasegroup.com/nsn/5950-00-244-5641
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.688 inches single mounting facility single center group
Overall Height:
4.406 inches
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
2.344 inches
Body Width:
2.344 inches
Body Height:
3.531 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Thready Qty Per Inch (tpi):
24 single group
Thread Size:
0.190 inches single group
Winding Operating Current:
650.0 milliamperes ac single component 1st secondary
Winding Operating Voltage:
115.00 ac volts single component single primary6.30 ac volts single component all secondary115.00 ac volts single component single
primary
Thread Series Designator:

Thread Series Designator

Unc single group

**Terminal Type And Quantity:** 

7 standoff, solder lug

Shelf Life:

N/a

## **NSN 5950-00-244-5641**Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A058b0