

View Online at <https://aerobasegroup.com/nsn/5950-00-245-0882>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group1.750 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

2.380 inches 2.380 inches

Body Height:

3.810 inches 3.810 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 6 secondary single component6 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

2.5 amperes ac single component all secondary

Winding Operating Voltage:

110.00 ac volts single component single primary and 6.30 ac volts single component all secondary115.00 ac volts single component single primary and 120.00 ac volts single component single primary

Special Features:

Filled with asphaltic potting compound

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

**Fiig:**

A058b0