

View Online at <https://aerobasegroup.com/nsn/5950-00-245-8756>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

2.750 inches

Body Width:

2.375 inches

Body Height:

2.812 inches

Maximum Operating Temp:

90.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

350.0 milliamperes dc single component single secondary

Winding Operating Voltage:

115.00 ac volts single component 1st primary115.00 ac volts single component 2nd primary115.00 ac volts single component 1st primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0