

View Online at <https://aerobasegroup.com/nsn/5950-00-246-5260>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.438 inches single mounting facility single center group3.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group1.750 inches single mounting facility single center group

Overall Height:

6.125 inches 6.125 inches

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

4.594 inches 4.594 inches

Body Width:

2.688 inches 2.688 inches

Body Height:

5.344 inches 5.344 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

20 single group20 single group

Thread Size:

0.250 inches single group0.250 inches single group

Winding Operating Current:

14.0 amperes ac single component single secondary

Winding Power Rating:

2.4 watts single component single primary

Winding Operating Voltage:

2.50 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0