NSN 5950-00-246-5273

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-246-5273

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.875 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.250 inches single mounting facility single center group |
| Frequency Rating: |
| 50.0 hertz and 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure single component |
| Body Length: |
| 3.656 inches |
| Body Width: |
| 3.281 inches |
| Body Height: |
| 4.312 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 6 single group |
| Mounting Method: |
| Flange and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary and 1 secondary single component |
| Winding Operating Current: |
| 6.0 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 5.00 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 9 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |
| |