

View Online at <https://aerobasegroup.com/nsn/5950-00-246-5277>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

5.375 inches

Body Width:

4.109 inches

Body Height:

4.562 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

750.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

210.00 ac volts single component single primary and 220.00 ac volts single component single primary and 230.000 ac volts single component single primary and 250.00 ac volts single component single primary

Terminal Type And Quantity:

11 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0