## NSN 5950-00-247-0904

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-247-0904

|    | eliability Indicator:                                                           |
|----|---------------------------------------------------------------------------------|
|    | lot established                                                                 |
|    | enter To Center Distance Between Mounting Facilities Parallel To Length         |
|    | .250 inches single mounting facility single center group                        |
|    | enter To Center Distance Between Mounting Facilities Parallel To Width:         |
|    | .812 inches single mounting facility single center group                        |
|    | nput-output Phase Relationship:<br>ingle phase to single phase single component |
|    | /inding Shielding Method:                                                       |
|    | Iternal shield brought out to terminal single component                         |
|    | ody Length:                                                                     |
|    | .688 inches                                                                     |
|    | ody Width:                                                                      |
|    | .375 inches                                                                     |
|    | ody Height:                                                                     |
|    | .875 inches                                                                     |
|    | nclosure Type:                                                                  |
|    | ully enclosed                                                                   |
|    | Iounting Facility Quantity:                                                     |
|    | single group                                                                    |
|    | lounting Method:                                                                |
|    | hreaded stud single group                                                       |
|    | /inding Function And Quantity:                                                  |
| 1  | primary single component and 1 secondary single component                       |
| Т  | hready Qty Per Inch (tpi):                                                      |
| 32 | 2 single group                                                                  |
| Т  | hread Size:                                                                     |
| 0. | .138 inches single group                                                        |
| Т  | hread Series Designator:                                                        |
| U  | Inc single group                                                                |
| T  | erminal Type And Quantity:                                                      |
| 5  | tab, solder lug                                                                 |
| S  | helf Life:                                                                      |
| N  | /a                                                                              |
| U  | nit Of Measure:                                                                 |
|    |                                                                                 |
| D  | emilitarization:                                                                |
| N  | 0                                                                               |
| F  | iig:                                                                            |
| A  | 058b0                                                                           |