## NSN 5950-00-247-8083

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-247-8083

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                   |
| 3.625 inches single mounting facility single center group                                   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                    |
| 4.125 inches single mounting facility single center group                                   |
| Frequency Rating:   |
| 57.0 hertz single component and 63.0 hertz single component                                 |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure single component                                      |
| Body Length:  |
| 5.313 inches  |
| Body Width:   |
| 4.563 inches  |
| Body Height:  |
| 5.938 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 2 secondary single component                                 |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.138 inches single group   |
| Winding Operating Current:  |
| 10.0 amperes ac single component 3rd secondary  |
| Winding Operating Voltage:  |
| 5.00 ac volts single component all secondary115.00 ac volts single component single primary |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 6 standoff, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

## NSN 5950-00-247-8083

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

