

View Online at <https://aerobasegroup.com/nsn/5950-00-247-8089>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.250 inches single mounting facility single center group2.250 inches single mounting facility single center group

**Overall Height:**

6.249 inches 6.249 inches

**Frequency Rating:**

58.0 hertz single component and 58.0 hertz single component and 62.0 hertz single component62.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

3.750 inches 3.750 inches

**Body Width:**

3.031 inches 3.031 inches

**Body Height:**

4.812 inches 4.812 inches

**Maximum Operating Temp:**

65.0 degrees celsius65.0 degrees celsius

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

**Thready Qty Per Inch (tpi):**

20 single group20 single group

**Thread Size:**

0.250 inches single group0.250 inches single group

**Winding Operating Current:**

900.0 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:**

6.35 ac volts single component 3rd secondary115.00 ac volts single component single primary6.50 ac volts single component 4th secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

11 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0