

View Online at <https://aerobasegroup.com/nsn/5950-00-247-8089>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group2.250 inches single mounting facility single center group

Overall Height:

6.249 inches 6.249 inches

Frequency Rating:

58.0 hertz single component and 58.0 hertz single component and 62.0 hertz single component62.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

3.750 inches 3.750 inches

Body Width:

3.031 inches 3.031 inches

Body Height:

4.812 inches 4.812 inches

Maximum Operating Temp:

65.0 degrees celsius65.0 degrees celsius

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

Thready Qty Per Inch (tpi):

20 single group20 single group

Thread Size:

0.250 inches single group0.250 inches single group

Winding Operating Current:

900.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

6.35 ac volts single component 3rd secondary115.00 ac volts single component single primary6.50 ac volts single component 4th secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0