

View Online at <https://aerobasegroup.com/nsn/5950-00-248-2324>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.813 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.430 inches single mounting facility single center group

Frequency Rating:

800.0 hertz single component and 1.2 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

2.938 inches

Body Width:

2.531 inches

Body Height:

2.531 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

48 single group

Thread Size:

0.112 inches single group

Winding Operating Voltage:

40.00 ac volts single component single primary and 240.00 ac kilovolts single component single secondary or 260.00 ac kilovolts single component single secondary or 50.00 ac volts single component single primary and 280.00 ac kilovolts single component single secondary 200.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

11 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0