# NSN 5950-00-249-3179

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-249-3179

# **Reliability Indicator:**

Not establishednot established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group3.750 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

# **Frequency Rating:**

60.0 hertz single component60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### **Body Length:**

5.125 inches 5.125 inches

#### **Body Width:**

4.375 inches 4.375 inches

#### **Body Height:**

5.250 inches 5.250 inches

#### **Inclosure Type:**

Hermetically sealedhermetically sealed

# **Mounting Facility Quantity:**

4 single group4 single group

# **Mounting Method:**

Threaded stud single groupthreaded stud single group

#### **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

# Thready Qty Per Inch (tpi):

40 single group40 single group

# Thread Size:

0.112 inches single group0.112 inches single group

#### **Winding Operating Current:**

110.0 milliamperes ac single component single secondary

# Winding Operating Voltage:

1.73 ac kilovolts single component single secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

9 tab, solder lug

#### Shelf Life:

N/a

# **Unit Of Measure:**

#### **Demilitarization:**

No

# NSN 5950-00-249-3179

Power Transformer - Page 2 of 2



Fiig:

A058b0