

View Online at <https://aerobasegroup.com/nsn/5950-00-249-3195>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.875 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

8.250 inches

**Body Width:**

6.906 inches

**Body Height:**

8.312 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thready Qty Per Inch (tpi):**

16 single group

**Thread Size:**

0.875 inches single group

**Winding Operating Current:**

1.28 amperes ac single component 3rd secondary

**Winding Operating Voltage:**

104.00 ac volts single component single primary and 650.00 ac volts single component all secondary 109.00 ac volts single component single primary and 115.00 ac volts single component single primary and 121.00 ac volts single component single primary and 127.00 ac volts single component single primary

**Thread Series Designator:**

Un single group

**Terminal Type And Quantity:**

10 standoff insulator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0