

View Online at <https://aerobasegroup.com/nsn/5950-00-249-3195>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.875 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

8.250 inches

Body Width:

6.906 inches

Body Height:

8.312 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

16 single group

Thread Size:

0.875 inches single group

Winding Operating Current:

1.28 amperes ac single component 3rd secondary

Winding Operating Voltage:

104.00 ac volts single component single primary and 650.00 ac volts single component all secondary 109.00 ac volts single component single primary and 115.00 ac volts single component single primary and 121.00 ac volts single component single primary and 127.00 ac volts single component single primary

Thread Series Designator:

Un single group

Terminal Type And Quantity:

10 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0