NSN 5950-00-249-3200

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-249-3200

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 6.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.125 inches single mounting facility single center group |
| Frequency Rating: |
| 50.0 hertz or 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure single component |
| Body Length: |
| 5.875 inches |
| Body Width: |
| 5.062 inches |
| Body Height: |
| 7.094 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 6 single group |
| Mounting Method: |
| Flange and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary and 1 secondary single component |
| Winding Operating Current: |
| 212.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 105.00 ac volts and 110.00 ac volts and 115.00 ac volts and 120.00 ac volts and 125.00 ac volts single component single primary |
| Terminal Type And Quantity: |
| 9 standoff, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |