

View Online at <https://aerobasegroup.com/nsn/5950-00-249-3239>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

7.000 inches single mounting facility single center group7.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.000 inches single mounting facility single center group6.000 inches single mounting facility single center group

**Overall Height:**

7.656 inches 7.656 inches

**Frequency Rating:**

60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single componentinternal shield grounded to core single component

**Body Length:**

8.750 inches 8.750 inches

**Body Width:**

7.750 inches 7.750 inches

**Body Height:**

6.500 inches 6.500 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thready Qty Per Inch (tpi):**

20 single group20 single group

**Thread Size:**

0.250 inches single group0.250 inches single group

**Winding Operating Current:**

400.0 milliamperes dc single component single secondary

**Winding Operating Voltage:**

640.00 ac volts single component single secondary115.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0