

View Online at <https://aerobasegroup.com/nsn/5950-00-249-3239>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.000 inches single mounting facility single center group7.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.000 inches single mounting facility single center group6.000 inches single mounting facility single center group

Overall Height:

7.656 inches 7.656 inches

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single component

Body Length:

8.750 inches 8.750 inches

Body Width:

7.750 inches 7.750 inches

Body Height:

6.500 inches 6.500 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

20 single group20 single group

Thread Size:

0.250 inches single group0.250 inches single group

Winding Operating Current:

400.0 milliamperes dc single component single secondary

Winding Operating Voltage:

640.00 ac volts single component single secondary115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0