NSN 5950-00-249-8827

Electrical Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-249-8827

Reliability Indicator:
Not established
Turn Quantity:
2840 single component single winding
Mounting Hole Diameter:
0.120 inches single group
Core Construction:
S0lid single component
Body Length:
1.062 inches
Body Width:
1.000 inches
Body Height:
1.188 inches
Distance Between Mounting Facility Centers:
0.750 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
mounting mounds.
Flange single group and unthreaded hole single group
-
Flange single group and unthreaded hole single group
Flange single group and unthreaded hole single group Rating Method:
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size:
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size: 0.00708 inches american wire gage single component single winding
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size: 0.00708 inches american wire gage single component single winding Dc Resistance Rating In Ohms:
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size: 0.00708 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 115.000 single component single winding
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size: 0.00708 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 115.000 single component single winding Terminal Type And Quantity:
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size: 0.00708 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 115.000 single component single winding Terminal Type And Quantity: 2 threaded stud
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size: 0.00708 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 115.000 single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life:
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size: 0.00708 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 115.000 single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size: 0.00708 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 115.000 single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size: 0.00708 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 115.000 single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:
Flange single group and unthreaded hole single group Rating Method: Winding turns single component single winding Winding Conductor Size: 0.00708 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 115.000 single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: