

View Online at <https://aerobasegroup.com/nsn/5950-00-250-2017>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.750 inches single mounting facility single center group1.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.750 inches single mounting facility single center group1.750 inches single mounting facility single center group

**Overall Height:**

1.700 inches 1.700 inches

**Frequency Rating:**

10.0 kilohertz single component10.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

**Body Length:**

2.515 inches 2.515 inches

**Body Width:**

2.515 inches 2.515 inches

**Body Height:**

1.400 inches 1.400 inches

**Maximum Operating Temp:**

105.0 degrees celsius105.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

50.0 milliamperes dc single component 1st secondary

**Winding Operating Voltage:**

7.50 ac volts single component 1st secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

9 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0