
## NSN 5950-00-250-7509

Pulse Transformer - Page 1 of 2





### **Reliability Indicator:**

Not established

#### Overall Length:

1.188 inches

### Mounting Hole Diameter:

0.147 inches single group

#### Inductance Rating:

7.78 millihenries single component single primary

#### Impedance Rating In Ohms:

7700.0 single component single primary

#### Primary To Secondary Turn Ratio:

1 to 1 to 1 single component

#### **Pulse Repetition Rate:**

600.0 hertz single component

#### **Body Length:**

0.938 inches

#### Body Outside Diameter:

0.875 inches

#### **Overall Diameter:**

1.438 inches

#### Maximum Operating Temp:

105.0 degrees celsius

#### **Distance Between Mounting Facility Centers:**

1.125 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

#### **Mounting Facility Quantity:**

2 single group

#### **Mounting Method:**

Unthreaded hole single group

#### Winding Function And Quantity:

1 primary single component and 2 secondary single component

#### Winding Operating Current:

10.0 milliamperes ac single component all secondary

#### Dc Resistance Rating In Ohms:

3.200 single component 2nd secondary

#### **Terminal Type And Quantity:**

6 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5950-00-250-7509

Pulse Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

