

View Online at <https://aerobasegroup.com/nsn/5950-00-250-8200>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.438 inches single mounting facility single center group

Mounting Slot Width:

0.200 inches single group

Frequency Rating:

47.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.310 inches

Body Width:

4.125 inches

Body Height:

3.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

7.0 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

25.00 ac volts single component single secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0