

View Online at <https://aerobasegroup.com/nsn/5950-00-251-4242>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

3.750 inches 3.750 inches

Body Width:

3.250 inches 3.250 inches

Body Height:

4.250 inches 4.250 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Voltage:

1.00 ac volts single component single primary and 1.50 ac volts single component single primary and 3.00 ac volts single component single primary and 8.00 ac volts single component single primary and 10.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0