

View Online at <https://aerobasegroup.com/nsn/5950-00-251-4242>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

3.750 inches 3.750 inches

**Body Width:**

3.250 inches 3.250 inches

**Body Height:**

4.250 inches 4.250 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thread Size:**

0.190 inches single group0.190 inches single group

**Winding Operating Voltage:**

1.00 ac volts single component single primary and 1.50 ac volts single component single primary and 3.00 ac volts single component single primary and 8.00 ac volts single component single primary and 10.00 ac volts single component single primary

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0