

View Online at <https://aerobasegroup.com/nsn/5950-00-251-4327>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.562 inches single mounting facility single center group5.562 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.750 inches single mounting facility single center group3.750 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

6.719 inches 6.719 inches

**Body Width:**

5.938 inches 5.938 inches

**Body Height:**

6.531 inches 6.531 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thread Size:**

0.250 inches single group0.250 inches single group

**Winding Operating Voltage:**

115.00 ac volts single component single primary170.00 ac volts single component single secondary and 715.00 ac volts single component single secondary and 885.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 standoff, threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0