NSN 5950-00-251-4328

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-251-4328

View Online at https://aerobasegroup.com/nsn/5950-00-251-4328
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
5.562 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.000 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
6.719 inches
Body Width:
5.188 inches
Body Height:
6.562 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
20 single group
Thread Size:
0.250 inches single group
Winding Operating Current:
370.0 milliamperes ac single component single secondary
Winding Operating Voltage:
890.00 ac volts single component single secondary115.00 ac volts single component single primary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
5 standoff, threaded stud
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-00-251-4328

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0