

View Online at <https://aerobasegroup.com/nsn/5950-00-251-4344>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.750 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

7.438 inches

Body Width:

6.875 inches

Body Height:

7.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Voltage:

115.00 ac volts single component single primary 265.00 ac volts single component single secondary and 855.00 ac volts single component single secondary and 1.12 ac kilovolts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0