NSN 5950-00-252-1161

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-252-1161

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus proof and moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.938 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.140 inches single group

Frequency Rating:

360.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

1.625 inches

Body Width:

1.312 inches

Body Height:

1.375 inches

Maximum Operating Temp:

80.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.3 amperes ac single component single secondary

Winding Operating Voltage:

11.00 ac volts single component single secondary

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-252-1161

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0