NSN 5950-00-252-1333

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-252-1333 **Reliability Indicator:** Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.437 inches single mounting facility single center group **Frequency Rating:** 47.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component **Body Length:** 3.375 inches **Body Width:** 2.750 inches **Body Height:** 1.500 inches Inclosure Type: Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group **Thread Size:** 0.112 inches single group Winding Operating Current: 75.0 milliamperes ac single component single secondary Winding Operating Voltage: 44.00 ac volts single component single secondary208.00 ac volts single component single primary **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No

NSN 5950-00-252-1333

Power Transformer - Page 2 of 2

Fiig: A058b0

