

View Online at <https://aerobasegroup.com/nsn/5950-00-252-1909>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

50.0 hertz or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.562 inches

Body Width:

4.109 inches

Body Height:

5.312 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange and unthreaded hole single group

Winding Function And Quantity:

1 primary and 2 secondary single component

Winding Operating Current:

3.5 amperes ac single component 2nd secondary

Winding Operating Voltage:

210.00 ac volts and 220.00 ac volts and 230.00 ac volts and 240.00 ac volts and 250.00 ac volts single component single primary

Terminal Type And Quantity:

6 threaded stud and 6 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0