NSN 5950-00-252-2655

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-252-2655

| view offilite at https://defobasegroup.com/hish/0550-00-252-2000 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.625 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.750 inches single mounting facility single center group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 4.750 inches |
| Body Width: |
| 3.062 inches |
| Body Height: |
| 5.031 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Current: |
| 47.0 milliamperes ac single component 2nd secondary |
| Winding Operating Voltage: |
| $800.00 \ \text{ac volts} \ \ \text{single component 1st secondary} 115.00 \ \text{ac volts} \ \ \text{single component single primary} 212.00 \ \text{ac volts} \ \ \text{single component 2nd}$ |
| secondary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 7 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-00-252-2655

Power Transformer - Page 2 of 2



Fiig:

A058b0